

PERFORMANCE

Processor

Processor Family

Up to two 205 W Gen 1 or Gen 2 Intel® Xeon® Scalable family processors, Bronze, Silver, Gold, or Platinum

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Xeon Bronze 3104	6	6	1.7GHz	-	8.25MB	DDR4-2133	-
Xeon Bronze 3106	8	8	1.7GHz	-	11MB	DDR4-2133	-
Xeon Bronze 3204	6	6	1.9GHz	1.9GHz	8.25MB	DDR4-2133	-
Xeon Bronze 3206R	8	8	1.9GHz	1.9GHz	11MB	DDR4-2133	-
Xeon Silver 4108	8	16	1.8GHz	3.0GHz	11MB	DDR4-2400	-
Xeon Silver 4110	8	16	2.1GHz	3.0GHz	11MB	DDR4-2400	-
Xeon Silver 4112	4	8	2.6GHz	3.0GHz	8.25MB	DDR4-2400	-
Xeon Silver 4114	10	20	2.2GHz	3.0GHz	13.75MB	DDR4-2400	-
Xeon Silver 4114T	10	20	2.2GHz	3.0GHz	13.75MB	DDR4-2400	-
Xeon Silver 4116	12	24	2.1GHz	3.0GHz	16.5MB	DDR4-2400	-
Xeon Silver 4208	8	16	2.1GHz	3.2GHz	11MB	DDR4-2400	-
Xeon Silver 4209T	8	16	2.2GHz	3.2GHz	11MB	DDR4-2400	-
Xeon Silver 4210	10	20	2.2GHz	3.2GHz	13.75MB	DDR4-2400	-
Xeon Silver 4210R	10	20	2.4GHz	3.2GHz	13.75MB	DDR4-2400	-
Xeon Silver 4214	12	24	2.2GHz	3.2GHz	16.5MB	DDR4-2400	-
Xeon Silver 4214R	12	24	2.4GHz	3.5GHz	16.5MB	DDR4-2400	-
Xeon Silver 4215	8	16	2.5GHz	3.5GHz	11MB	DDR4-2400	-
Xeon Silver 4215R	8	16	3.2GHz	4.0GHz	11MB	DDR4-2400	-
Xeon Silver 4216	16	32	2.1GHz	3.2GHz	22MB	DDR4-2400	-
Xeon Gold 5115	10	20	2.4GHz	3.2GHz	13.75MB	DDR4-2400	-
Xeon Gold 5118	12	24	2.3GHz	3.2GHz	16.5MB	DDR4-2400	-
Xeon Gold 5120	14	28	2.2GHz	3.2GHz	19.25MB	DDR4-2400	-
Xeon Gold 5120T	14	28	2.2GHz	3.2GHz	19.25MB	DDR4-2400	-
Xeon Gold 5122	4	8	3.6GHz	3.7GHz	16.5MB	DDR4-2666	-
Xeon Gold 5215	10	20	2.5GHz	3.4GHz	13.75MB	DDR4-2666	-
Xeon Gold 5217	8	16	3.0GHz	3.7GHz	11MB	DDR4-2666	-
Xeon Gold 5218	16	32	2.3GHz	3.9GHz	22MB	DDR4-2666	-
Xeon Gold 5220	18	36	2.2GHz	3.9GHz	24.75MB	DDR4-2666	-
Xeon Gold 5222	4	8	3.8GHz	3.9GHz	16.5MB	DDR4-2933	-
Xeon Gold 6128	6	12	3.4GHz	3.7GHz	19.25MB	DDR4-2666	-
Xeon Gold 6130	16	32	2.1GHz	3.7GHz	22MB	DDR4-2666	-
Xeon Gold 6134	8	16	3.2GHz	3.7GHz	24.75MB	DDR4-2666	-
Xeon Gold 6136	12	24	3.0GHz	3.7GHz	24.75MB	DDR4-2666	-
Xeon Gold 6138	20	40	2.0GHz	3.7GHz	27.5MB	DDR4-2666	-
Xeon Gold 6142	16	32	2.6GHz	3.7GHz	22MB	DDR4-2666	-
Xeon Gold 6146	12	24	3.2GHz	4.2GHz	24.75MB	DDR4-2666	-
Xeon Gold 6148	20	40	2.4GHz	3.7GHz	27.5MB	DDR4-2666	-

Xeon Gold 6154	18	36	3.0GHz	3.7GHz	24.75MB	DDR4-2666	-
Xeon Gold 6226	12	24	2.7GHz	3.7GHz	19.25MB	DDR4-2933	-
Xeon Gold 6226R	16	32	2.9GHz	3.9GHz	22MB	DDR4-2933	-
Xeon Gold 6230	20	40	2.1GHz	3.9GHz	27.5MB	DDR4-2933	-
Xeon Gold 6234	8	16	3.3GHz	4.0GHz	24.75MB	DDR4-2933	-
Xeon Gold 6238T	22	44	1.9GHz	3.7GHz	30.25MB	DDR4-2933	-
Xeon Gold 6240R	24	48	2.4GHz	4.0GHz	35.75MB	DDR4-2933	-
Xeon Gold 6242	16	32	2.8GHz	3.9GHz	22MB	DDR4-2933	-
Xeon Gold 6244	8	16	3.6GHz	4.4GHz	24.75MB	DDR4-2933	-
Xeon Gold 6246	12	24	3.3GHz	4.2GHz	24.75MB	DDR4-2933	-
Xeon Gold 6248	20	40	2.5GHz	3.9GHz	27.5MB	DDR4-2933	-
Xeon Gold 6254	18	36	3.1GHz	4.0GHz	24.75MB	DDR4-2933	-
Xeon Gold 6258R	28	56	2.7GHz	4.0GHz	38.5MB	DDR4-2933	-
Xeon Platinum 8160T	24	48	2.1GHz	3.7GHz	33MB	DDR4-2666	-
Xeon Platinum 8180	28	56	2.5GHz	3.8GHz	38.5MB	DDR4-2666	-
Xeon Platinum 8280	28	56	2.7GHz	4.0GHz	38.5MB	DDR4-2933	-
Xeon W-3223	8	16	3.5GHz	4.0GHz	16.5MB	DDR4-2666	-
Xeon W-3225	8	16	3.7GHz	4.3GHz	16.5MB	DDR4-2666	-
Xeon W-3235	12	24	3.3GHz	4.4GHz	19.25MB	DDR4-2933	-
Xeon W-3245	16	32	3.2GHz	4.4GHz	22MB	DDR4-2933	-
Xeon W-3265	24	48	2.7GHz	4.4GHz	33MB	DDR4-2933	-
Xeon W-3275	28	56	2.5GHz	4.4GHz	38.5MB	DDR4-2933	-

Processor Sockets

2x FCLGA3647

Operating System

- Windows® 10 Pro 64 for Workstations
- Ubuntu Linux LTS
- No operating system

Graphics**Discrete Graphics Support**

Supports up to two NVIDIA® Quadro® RTX 8000 with NVLink

Discrete Graphics Offering

Graphics	Memory	Power	Connector	SLI / NVlink
NVS 810	4GB DDR3	68W	8x miniDP	None
Quadro P400	2GB GDDR5	30W	3x miniDP	None
Quadro P600	2GB GDDR5	45W	4x miniDP	None
Quadro P620	2GB GDDR5	40W	4x miniDP	None
Quadro P1000	4GB GDDR5	50W	4x miniDP	None
Quadro P2000	5GB GDDR5	75W	4x DP	None
Quadro P2200	5GB GDDR5	75W	4x DP	None
Quadro P4000	8GB GDDR5	120W	4x DP	None
Quadro P5000	16GB GDDR5X	180W	1x DVI-D DL, 4x DP	SLI
Quadro P6000	24GB GDDR5X	250W	1x DVI-D DL, 4x DP	SLI
Quadro RTX 4000	8GB GDDR6	160W	3x DP, 1x VirtualLink	None

Quadro RTX 5000	16GB GDDR6	265W	4x DP, 1x VirtualLink	NVLink
Quadro RTX 6000	24GB GDDR6	295W	4x DP, 1x VirtualLink	NVLink
Quadro RTX 8000	48GB GDDR6	295W	4x DP, 1x VirtualLink	NVLink
Quadro GP100	16GB HBM2	235W	1x DVI-D DL, 4x DP	NVLink
Quadro GV100	32GB HBM2	250W	4x DP	NVLink

Monitor Support

Supports multiple displays via discrete graphics

Chipset

Intel C621 chipset

Memory

Memory Type

- DDR4-2666 LRDIMM ECC
- DDR4-2666 RDIMM ECC
- DDR4-2933 RDIMM ECC

Memory Slots

16 DIMM sockets with 12 channels. 8 DIMM sockets with 6 channels per processor

Memory Protection

ECC

Max Memory

Up to 1TB (DDR4-2666 LRDIMM or DDR4-2933 RDIMM) or 512GB (DDR4-2666 RDIMM)

Notes:

- The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support

Up to 6x 3.5" SATA HDD / 10x 2.5" SATA HDD / 8x 2.5" SAS HDD / 10x 2.5" SATA SSD / 4x 2.5" PCIe SSD + 9x M.2 PCIe SSD + 2x PCIe AIC SSD

- 3.5" HDD up to 4TB each
- 2.5" SATA HDD up to 500GB each
- 2.5" SAS HDD up to 600GB each
- 2.5" SATA SSD up to 2TB each
- M.2 SSD up to 2TB each
- PCIe AIC SSD up to 480GB each

Storage Controllers

Storage Controller	Type	Interface	RAID	Cache
Onboard Intel RST SATA RAID	Standard	SATA 6.0Gb/s	0/1/10/5	None
9440-8i PCIe	Optional	SAS 12.0Gb/s, SATA 6.0Gb/s	0/1/10/5	None
9460-16i PCIe	Optional	SAS 12.0Gb/s, SATA 6.0Gb/s	0/1/10/5/6	4GB DDR4, SuperCap
NVMe Basic	Optional	PCIe NVMe	0/1/10	None
NVMe Premium	Optional	PCIe NVMe	0/1/10/5	None
NVMe for Intel SSD	Optional	PCIe NVMe	0/1/10/5	None

Storage Type

Disk Type	Interface	RPM	Offering
3.5" SATA HDD	SATA 6Gb/s	7.2K	1TB/2TB/4TB/6TB
2.5" SATA HDD	SATA 6Gb/s	7.2K	500GB/500GB FIPS
2.5" SAS HDD	SAS 12Gb/s	10K	300GB/600GB

ThinkStation P920

2.5" SATA SSD	SATA 6Gb/s	-	256GB/512GB/1TB/2TB
2.5" PCIe SSD	PCIe NVMe	-	1.5TB
M.2 PCIe SSD	PCIe NVMe	-	256GB/512GB/1TB/2TB
PCIe AIC SSD	PCIe NVMe	-	480GB

Removable Storage

Optical Support

Up to three HH or two 9.0mm optical drives, DVD-ROM, DVD±RW, or Blu-ray

Card Reader

- SD card reader
- 15-in-1 card reader
- No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC662 codec

Power Supply

Power	Type	Efficiency	Key Features
1400W	Fixed	92%	Autosensing, 80 PLUS Platinum qualified. Countries with input voltage under 115V, output power limited to 1125 watts

DESIGN

Mechanical

Form Factor

Tower (55L)

Dimensions (WxDxH)

200 x 620 x 446 mm (7.87 x 24.4 x 17.56 inches, with feet)

Weight

37 kg (81.6 lbs, maximum configuration)

Bays

- 2x 3.5" disk bay (standard)
- 4x 3.5" disk bay (optional):
2 bays come with 3rd disk or Storage Bay Upgrade Kit
2 bays via Flex bay

Notes:

- 4x 3.5" bay can also support up to 8x 2.5" SSD / HDD with 2 disks per bay. Additional 9440-8i or 9460-16i PCIe adapter and other parts are needed

Flex Bays

3x Flex bay, supports following:

- 3x half-height optical drives
- 2x 5.25" 9.0mm optical drives
- 1x 5.25" 9.0mm optical drive + 1x 3.5"/2.5" SATA SSD/HDD
- 1x 3.5"/2.5" SATA SSD/HDD with Front Access Storage Enclosure
- 1x flex module for the following options:

Tray 1: 9.0mm optical

Tray 2: 15-in-1 USB 3.2 Gen 1 reader or 2x Thunderbolt™

Port 1 and 2: Front USB 3.2 Gen 1 Type-C or eSATA

- 3x M.2 SSD with 3x Front Removable Drive Enclosures

M.2 Slots

Up to 9x M.2 SSD:

- 2 via onboard slots

- 4 via Quad M.2 to PCIe adapter
- 3 via Single M.2 to PCIe adapters

Expansion Slots

- Five PCIe 3.0 x16 (2nd CPU needed)
- Three PCIe 3.0 x4

Expansion Slots Offering

Slot 1 (CPU1) PCIe 3.0 x16, full height, full length, 75W, double-width, by CPU1

Slot 2 (CPU1) PCIe 3.0 x4, full height, full length, 25W, open ended, by CPU1

Slot 3 (CPU1) PCIe 3.0 x16, full height, full length, 75W, double-width, by CPU1

Slot 4 (CPU1) PCIe 3.0 x4, full height, full length, 25W, open ended, by CPU1

Slot 5 (PCH) PCIe 3.0 x4, full height, half length, 25W, open ended, by PCH

Slot 6 (CPU2) PCIe 3.0 x16, full height, half length, 75W, by CPU2

Slot 7 (CPU2) PCIe 3.0 x16, full height, full length, 75W, double-width, by CPU2

Slot 8 (CPU2) PCIe 3.0 x16, full height, full length, 75W, by CPU2

CONNECTIVITY

Network

Onboard Ethernet

Two gigabit Ethernet, Intel Ethernet Connection I219-LM and I210-AT, 2x RJ45, supports Wake-on-LAN

Optional Ethernet

Additional Ethernet options via PCIe adapter

WLAN + Bluetooth™

- Intel Dual Band Wireless-AC 8265, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 4.2
- No WLAN and Bluetooth

Ports

Front Ports

- 1x USB 3.1 Gen 1 (Always On and fast charge)
- 3x USB 3.1 Gen 1
- 1x headphone / microphone combo jack (3.5mm)

Notes:

- The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

Thunderbolt 3: 40 Gbit/s;

FireWire 400: 400 Mbit/s;

FireWire 800: 800 Mbit/s;

Optional Front Ports

- 1x eSATA (with flex module)
- 2x Thunderbolt (with flex module, USB-C form, one supports video-out)
- 1x USB-C 3.1 Gen 1 (with flex module)

Rear Ports

- 2x USB 2.0
- 4x USB 3.1 Gen 1
- 2x PS/2 ports (keyboard/mouse)
- 2x Ethernet (RJ-45)
- 1x microphone (3.5mm)
- 1x line-in (3.5mm)
- 1x line-out (3.5mm)

Notes:

- For video ports on discrete graphics, please see graphics section

Optional Rear Ports

- 2x USB-C 3.1 Gen 2 (via 2-port USB-C expansion card)
- 1x Thunderbolt
- 1x serial

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0, TCG certified

Physical Locks

- (Optional) Access Panel Lock Kit with Common Key
- (Optional) Access Panel Lock Kit with Unique Key
- Kensington® Security Slot

Chassis Intrusion Switch

Chassis intrusion switch

BIOS Security

- Power-on password
- Administrator password

MANAGEABILITY

System Management

Intel vPro with Intel AMT 11

Diagnostic

- Photo-audio transfer with Lenovo PC Diagnostics for Android and iOS
- ThinkStation® Diagnostics for Windows
- Front 4-digit diagnostic

SERVICE

Warranty

Base Warranty

3-year limited onsite service (with 9x5 NBD, for most models)

ENVIRONMENTAL

Environmental Specifications

Temperature

Operating: 10° C to 35° C (50° F to 95° F)

Storage: -40°C to 60°C (-40°F to 140°F) in original shipping carton

Storage: -10°C to 60°C (14°F to 140°F) without carton

Altitude

Operating: -15.2m to 3048m (-50ft to 10000ft)

Storage: -15.2m to 10668m (-50ft to 35000ft)

Humidity

Relative Humidity Operating: 10% to 80% (non-condensing)

Relative Humidity Storage/Transit: 10% to 90% (non-condensing)

Wet Bulb Temperature Operating: 25°C (77°F) max

Wet Bulb Temperature Non-operating: 40°C (104°F) max

CERTIFICATIONS

Green Certifications

- EPEAT™ Silver
- ENERGY STAR® 8.0 (On model 30BC003WUS)
- GREENGUARD®
- RoHS compliant

ISV Certifications

Please visit www.thinkworkstations.com/isv-certifications/

